

SUBMITTAL - 09KPAS1

Job Name:_____

Date:_____

Location:_____

Indoor Unit: **ASUH09KPAS**

Outdoor Unit: **AOUH09KPAS1**



FEATURES

INDOOR UNIT:

- Compact wall-mounted indoor unit delivering superior comfort and energy-efficient performance
- Indoor unit with ProCore™ (High Corrosion Resistant Copper) coils for long-lasting protection against corrosion
- Whisper-quiet operation with sound levels as low as 19dB
- Multiple fan speed options; Auto, High, Med-High, Med, Med-Low, Low, and Quiet.
- Special Operation modes available:
 - Economy Mode / Energy Saving Mode / Powerful Mode / Minimum Heat Mode / Automatic defrosting operation / Auto-restart function
- Enhanced controls platform for seamless, intuitive operation:
 - Backlit wireless remote controller with luminous buttons for easy visibility, included with the indoor unit
 - Wi-Fi connectivity with Airstage Mobile App monitoring via compatible USB WLAN adapter
 - Extended connectivity with support for third-party interface options
 - Compatible with BACnet and Modbus protocols for seamless integration with building management and Home Automation Systems
- Advanced scheduling and timer options offer greater control over unit operation:
 - Weekly Timer / 24-hr Timer / Sleep Function
- Dual-action Filtration: Apple-Catechin Filter & Ion Deodorizing Filter
- Additional premium features include, but are not limited to:
 - Built-in external input and output for interlocking systems with 3rd party devices (Ex: Fire Alarm, Door Switch, Humidifier, Aux. Heat & more)
 - Multiple Auxiliary Heat logic for optimized heating performance
 - Service monitoring functionality via compatible accessories (UTY-RVRU & UTY-RNRUZ-series)

OUTDOOR UNIT:

- Low GWP R-32 systems for reduced environmental impact
- INVERTER-driven compressor that offers superior performance, comfort, and energy savings
- Compact outdoor unit with extended line set lengths up to 66ft (20m)
- Up to 16% higher rated heating capacity than nominal capacity
- Low-noise outdoor unit operation mode
- Hydro Fin-coated heat exchanger for improved corrosion resistance and coil durability



7 Year Compressor, 5 Year Parts out-of-the-box Warranty.



10 Year Compressor, 10 Year Parts Warranty when registered within 60 days of installation in a residence.



12 Year Compressor, 12 Year Parts Warranty when registered within 60 days of installation and installed by a Fujitsu Elite contractor.



Due to continuous product improvements, specifications are subject to change without notice. Please log in to the Fujitsu Portal for the most up-to-date documentation <https://connect.fujitsugeneral.com>

Version: 20241118A

-1 of 6-

SUBMITTAL - 09KPAS1

SPECIFICATIONS:

Indoor Unit					ASUH09KPAS			
Outdoor Unit					AOUH09KPAS1			
System Name					09KPAS1			
AHRI Number					215212609			
SEER2		Cooling			Btu/hW	26		
EER2						12.5		
HSPF2		Heating			kW/kW	10.8		
COP2						4.18		
Outdoor Operation Range		Cooling			°F (°C)	14 to 122* ⁸ (-10 to 50* ⁸)		
		Heating				5 to 75 (-15 to 24)		
Indoor Capacity		Cooling		Rated	Btu/h	9000		
				Min.—Max.		3,100—11,200		
		Heating	47°FDB (Outdoor temp.)			Rated	10000	
			17°FDB (Outdoor temp.) ¹			Min.—Max.	2,400—13,600	
						Rated	6400	
			5°FDB (Outdoor temp.) ²			Max.	9000	
						Rated	7100	
			Max.					
Outdoor Connection pipe		Liquid		in (mm)	Ø1/4 (Ø6.35)			
		Gas			Ø3/8 (Ø9.52)			
		Method			FLARE			
		Pre-charge length			ft (m)	49 (15)		
		Min. length				10 (3)		
		Max. length				66 (20)		
		Max. height difference				49 (15)		
Indoor Dimensions (H × W × D)		Net			in (mm)	10-5/8 × 32-13/16 × 8-3/4 (270 × 834 × 222)		
		Gross				10-7/8 × 36 × 13-1/16 (277 × 914 × 332)		
Indoor Weight		Net			lb (kg)	21 (9.5)		
		Gross				26 (12.0)		
Outdoor Dimensions (H × W × D)		Net			in (mm)	21-5/16 × 26-1/8 × 11-7/16 (541 × 663 × 290)		
		Gross				23-11/16 × 31-5/8 × 14-3/4 (602 × 804 × 375)		
Outdoor Weight		Net			lb (kg)	51 (23)		
		Gross				57 (26)		
Indoor Fan		Cooling		High	CFM (m³/h)	394 (670)		
				Med—High		365 (620)		
				Med		318 (540)		
				Med—Low		283 (480)		
				Low		247 (420)		
				Quiet		153 (260)		
		Heating		High		430 (730)		
				Med—High		365 (620)		
				Med		336 (570)		
				Med—Low		300 (510)		
				Low		265 (450)		
				Quiet		188 (320)		
		Type × Qty					CROSSFLOW FAN × 1	
		Motor output				W	30	
		Outdoor Fan	Airflow rate	Cooling		CFM (m³/h)	936 (1,590)	
				Heating			959 (1,630)	
			Type × Qty			PROPELLER FAN × 1		
			Motor output			W	23	
Indoor Sound Pressure Level* ⁴		Cooling		High	dB (A)	40		
				Med—High		38		
				Med		34		
				Med—Low		32		
				Low		29		
				Quiet		19		
		Heating		High		42		
				Med—High		38		
				Med		36		
				Med—Low		33		
				Low		31		
				Quiet		21		
Outdoor Sound Pressure Level* ⁴		Cooling			46			
		Heating			48			

SUBMITTAL - 09KPAS1

SPECIFICATIONS:

Outdoor Refrigerant		Type		R32	
		Charge	lb oz	1 lb 5 oz	
			g	600	
Additional Charge Calculation				oz/ft	0.22
				g/m	20
Outdoor Refrigerant Oil		Type		RB74AF	
		Amount	in ³ (cm ³)	14.6 (240)	
Indoor Moisture removal			pints/h (L/h)	2.40 (1.12)	
Indoor Drain hose		Material		POLYPROPYLENE + HIGH-DENSITY POLYETHYLENE	
		Tip Diameter	in (mm)	I.D.: Ø17/32 (Ø13.8), O.D.: Ø19/32 to Ø21/32 (Ø15.0 to Ø16.8)	
Indoor Operation range		Cooling	°F (°C)	64 to 90 (18 to 32)	
			%RH	80 or less	
		Heating	°F (°C)	60 to 86 (16 to 30)	
Power Supply				208/230 V~ 60 Hz	
Available Voltage Range				187—253	
System power supply		Voltage		V	
		Frequency		Hz	
		Available voltage range		V	
Indoor Current	Cooling		A	3.5	
	Heating			3.4	
Maximum Operating Current* ³				Cooling	6.4
				Heating	7.9
Outdoor Starting Current				3.5	
MCA* ⁵				9.7	
Wiring spec.* ⁶				15	
Indoor Input Power	Cooling			Rated	0.72
			Min.—Max.	0.12—1.13	
	Heating	Rated	0.7		
		Min.—Max.	0.11—1.18		
		Rated	0.61		
		Max.	1		
		Rated	0.915		
		Max.			
Indoor Power Factor		Cooling		89.4	
		Heating		89.5	
Energy Star				ES, ESME	

NOTES

- Cooling: Indoor temperature of 80°F (26.7°CDB)/67°FWB (19.44°CWB), and outdoor temperature of 95°FDB (35°CDB)/75°FWB (23.9°CWB).
- Heating: Indoor temperature of 70°FDB (21.1°CDB)/60°FWB (15.56°CWB), and outdoor temperature of 47°FDB (8.33°CDB)/43°FWB (6.11°CWB).
- 17°FDB (Outdoor temp.) —*1: Heating (17°F): Indoor temperature of 70°FDB (21.1°CDB)/60°FWB (15.56°CWB), and outdoor temperature of 17°FDB (-8.33°CDB)/15°FWB (-9.44°CWB).
- 5°FDB (Outdoor temp.) —*2: Heating (5°F): Indoor temperature of 70°FDB (21.1°CDB)/60°FWB (15.56°CWB), and outdoor temperature of 5°FDB (-15.0°CDB)/4°FWB (-15.56°CWB).
- Test conditions are based on AHRI 210/240 2023.
- *4:
- Indoor Sound Pressure Level —Measured values in manufacturer's anechoic chamber.
- Outdoor Sound Pressure Level —Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here.
- *3:
- Maximum Operating Current —Maximum current is maximum value when operated within the operation range.
- The total current of indoor unit and outdoor unit.
- MCA —*5: Minimum Circuit Ampacity (Calculation based on UL60335-2-40)
- Wiring spec. —*6: Selected sample based on Japan Electrotechnical Standards and Codes Committee ED005.
- As the regulations of wire size and circuit breaker differ in each country or region, select appropriate devices complied to the regional standard.
- MAX. CKT. BKR —*7: Maximum Circuit Breaker
- Operation Range —*8: Suction temperature of the outdoor unit.
- System continues to operate below rated outdoor operation temperature range, subject to varying conditions. System has no low temperature cut out. Capacity is not tested outside of the rated temperature range.

SUBMITTAL - 09KPAS1

ACCESSORIES:

Model Number	Description
UTY-RVRU ^{*1}	KAGAMI - Touch Panel Wired Controller
UTY-RNRUZ5 ^{*1}	Touch Panel Wired Remote Controller
UTY-RHRY ^{*1}	Simple Wired Remote (Without Mode Function) - Hospitality
UTY-RSRY ^{*1}	Simple Wired Remote (With Mode Function)
UTY-TWRXZ2	Communication Kit - Wall Mount
UTY-TFSXH4	Wi-Fi Adapter (WiFi Interface Module USB Type)
FJ-AC-WIFI-1	Intesis Wi-Fi Device: Wired Module
FJ-IR-WIFI-1NA	Intesis IR Wireless AC Cloud Control Interface (Intesis Home app)
Breez MAX BM101-102WA	Cielo IR Controller w/ WiFi
UTY-VMSX	Modbus Converter
UTY-VTGX ^{*1}	Network Converter - Convert H-Series Comm. Protocol to V/J-Series Comm.
FJ-AC-485-1	Intesis - BACnet MSTP & Modbus RTU Gateway
UTY-TERX ^{*1}	External Switch Controller
UTY-TTRXZ1 ^{*1, 2}	24V Thermostat Interface
TTRXZ1-KIT ^{*1, 2}	24V Thermostat Interface Kit (UTY-TTRXZ1, UTY-WiFi Plug & 24V Transformer)
UTY-XCSXZ2	External input and output PCB
UTY-XWZX	External Wire Kit
UTY-XWZXZ5	External Connect Kit
UTY-DSGYZ2 ^{*3}	Airstage Edge Controller

NOTES:

*1 -Requires Communication kit UTY-TWRXZ2 to connect this device to IDU.

*2 -This device may not be used with any other type of controls (central controller, wire/wireless RC, WiFi adapter, BMS interface).

*3 -Connection to AIRSTAGE Cloud requires a compatible AIRSTAGE Mobile adapter connected to the IDU.

SUBMITTAL - 09KPAS1

OUTDOOR UNIT DIMENSIONS:

Unit: in (mm)

