



Bellwether®
60" x 30-1/4" alcove bath, right drain
K-838

Features

- Clean lines and streamlined style add contemporary appeal to any bathroom
- 14" apron height for easy entry and exit
- Standard size simplifies remodeling
- Integral flange helps prevent water from seeping behind wall and simplifies alcove installation
- Safeguard® slip-resistant surface provides excellent traction underfoot
- Wide ledges for extra storage space
- Integral apron
- Integral lumbar support

Material

- KOHLER® enameled cast iron

Installation

- Right drain
- Alcove
- Alcove

Recommended Products/Accessories

K-7213 27" Cable Bath Drain
K-7214 27" Cable Bath Drain
K-706000-D3 Frameless Sliding Bath Door
K-706000-L 62" H sliding bath door with 1/4"-thick glass
K-706004-D3 Frameless Sliding Bath Door
K-706004-L Frameless Sliding Bath Door
K-23726 Drain treatment
K-23725 Cast iron cleaner



ADA

Codes/Standards

ASME A112.19.1/CSA B45.2
ASTM F462
ADA
ICC/ANSI A117.1

KOHLER® Enameled Cast Iron Bath and Shower Base Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	17	Teal
	34	Fresh Green
	42	Aspen Green

Bellwether®
60" x 30-1/4" alcove bath, right drain
K-838

No change in measurement if connected with drain illustrated. (K-37383)

Rim Flange Detail

1/4" (6 mm)

1/2" (13 mm)

5/8" (16 mm)

60" (1524 mm)

8-1/2" (216 mm)

14-1/2" (368 mm)

3" (76 mm)

1/2" (13 mm)

30-1/4" (768 mm)

Lumbar Angle 29°

14" (356 mm)

1-1/2" Bath Drain

1/4" (6 mm)

4-1/8" (105 mm)

3-1/4" (83 mm)

Drain location:	Right
Basin area, bottom:	48-3/4" x 19-5/16" (1238 mm x 491 mm)
Basin area, top:	54-11/16" x 21-3/16" (1389 mm x 538 mm)
Weight:	310 lbs (140.6 kg)
Minimum floor load:	52 lbs/ft ² (253.9 kg/m ²)
Water depth:	9" (229 mm)
Water capacity:	32.6 gal (123.4 L)
Minimum flat for door:	2-5/8" (66 mm)

ADA compliant when installed to the specific requirements of these regulations.