



2TEC3F18 - 60B1000A 1-1/2 — 5 Ton

Air Handlers Convertible and Air-Tite™ for R-22

Specifications: Horizontal with vertical convertibility R-22 Air-Tite™

Model Number	Power Supply	Nominal Cap. Clg. (BTUH)	Ref. Con.	TXV Type	Fan Speed	Uncrated Dimensions(In.)			Mfg. Plant	Shipping Weight
						H	W	D		
2TEC3F18B1000A	200/230/1/60	18,000	BZ	Non-Bleed	3	43	21.5	21	VI	114
2TEC3F24B1000A	200/230/1/60	24,000	BZ	Non-Bleed	3	43	21.5	21	VI	121
2TEC3F30B1000A	200/230/1/60	30,000	BZ	Non-Bleed	3	45	21.5	21	VI	121
2TEC3F36B1000A	200/230/1/60	36,000	BZ	Non-Bleed	3	45	21.5	21	VI	135
2TEC3F42B1000A	200/230/1/60	42,000	BZ	Non-Bleed	4	51.8	23.5	21	VI	165
2TEC3F48B1000A*	200/230/1/60	48,000	BZ	Non-Bleed	3	57.9	23.5	21	VI	188
2TEC3F55B1000A	200/230/1/60	58,000	BZ	Non-Bleed	3	57.9	26.0	21	VI	193
2TEC3F60B1000A*	200/230/1/60	60,000	BZ	Non-Bleed	4	57.9	23.5	21	VI	193

* Two piece cabinet

Accessories:

Model Number	Description	Used With	Mfg. Plant	Shipping Weight
Extended Warranties – (See Extended Warranty Section)				
BAYSPEK140B	Single Power Entry Kit	BAYHTR1415BRKB, BAYHTR1419BRKB	VI	5
TAYPLNM100①	Pedestal Plenum Upflow	2TEC3F18-60B1000A	VI	10
TAYBASE101	Downflow Subbase	2TEC3F18-36B1000A	VI	12
TAYBASE100	Downflow Subbase	2TEC3F42-60B1000A	VI	16
BAY99X123	Knockout Cover Plate	2TEC3F18-60B1000A	TR	*

① For TEC018,024,030, center on plenum for 2" difference in width.

* Minimum Order 1 unit (1 unit = 50 pcs.)

Heaters:

Model Number	Power Supply		Power Supply		Mfg. Plant	Shipping Weight
	208/1/60 KW	208/1/60 BTUH	240/1/60 KW	240/1/60 BTUH		
BAYHTR1405000	3.60	12,300	4.80	16,400	VI	7
BAYHTR1405BRK	3.60	12,300	4.80	16,400	VI	9
BAYHTR1405PDC	3.60	12,300	4.80	16,400	VI	9
BAYHTR1408000	5.76	19,700	7.68	26,200	VI	8
BAYHTR1408BRK	5.76	19,700	7.68	26,200	VI	9
BAYHTR1408PDC	5.76	19,700	7.68	26,200	VI	9
BAYHTR1410000	7.20	24,600	9.60	32,800	VI	8
BAYHTR1410BRK	7.20	24,600	9.60	32,800	VI	9
BAYHTR1410PDC	7.20	24,600	9.60	32,800	VI	9
BAYHTR1415BRK	11.53	39,300	15.36	52,400	VI	11
BAYHTR1419BRK	14.42	49,200	19.20	65,500	VI	18
BAYHTR1425BRK	18.73	63,900	24.96	85,200	VI	18
		208/3/60		240/3/60		
BAYHTR3410000	7.20	24,600	9.60	32,800	VI	8
BAYHTR3415000	11.53	39,300	15.36	52,400	VI	10

000 = Pigtailed only, BRK = Contains Circuit Breakers, PDC = Pull Disconnect

Features:

- 13.0 SEER
- Ships in a vertical position - convertible for left hand horizontal applications.
- Six- way convertibility-horizontal (left & right); front & rear access; upflow, downflow
- Compact 21" depth for easy installation
- Corrosion resistant galvanized metal with attractive finish
- Superior condensate performance
- Enhanced internally finned coil tubes
- Five ton model with direct drive ECM motor
- Versatile duct flange - allows flush fit 3/4", 1", or 1.5" duct insulation
- Filter panel stamped with word "filter"
- 200/230 volt primary & 24 volt secondary transformer
- Low voltage wire nut connections
- Insulated cabinet
- External access to heater circuit breakers
- Polarized plugs for making electrical connections from air handler control box to heaters
- Factory installed non-bleed TXV with mechanical fitting
- Easy Air-Tite™ access to filter
- Approved for modular or manufactured homes
- Meets or exceeds Florida's 2% leakage criteria
- **5-year limited parts warranty**
- **Optional extended warranties**



4TEC3F18 - 60B1000A 1-1/2 — 5 Ton

Air Handlers Convertible and Air-Tite™ for R-410A

Specifications: Horizontal with vertical convertibility R-410A Air-Tite™

Model Number	Power Supply	Nominal Cap. Clg. (BTUH)	Ref. Con.	TXV Type	Fan Speed	Uncrated Dimensions(In.)			Mfg. Plant	Shipping Weight
						H	W	D		
4TEC3F18B1000A	200/230/1/60	18,000	BZ	Non-Bleed	3	43	21.5	21	VI	114
4TEC3F24B1000A	200/230/1/60	24,000	BZ	Non-Bleed	3	43	21.5	21	VI	121
4TEC3F30B1000A	200/230/1/60	30,000	BZ	Non-Bleed	3	45	21.5	21	VI	121
4TEC3F36B1000A	200/230/1/60	36,000	BZ	Non-Bleed	3	45	21.5	21	VI	135
4TEC3F42B1000A	200/230/1/60	42,000	BZ	Non-Bleed	4	51.8	23.5	21	VI	165
4TEC3F48B1000A*	200/230/1/60	48,000	BZ	Non-Bleed	3	57.9	23.5	21	VI	188
4TEC3F55B1000A	200/230/1/60	58,000	BZ	Non-Bleed	3	57.9	26.0	21	VI	193
4TEC3F60B1000A*	200/230/1/60	60,000	BZ	Non-Bleed	4	57.9	23.5	21	VI	193

* Two piece cabinet

Accessories:

Model Number	Description	Used With	Mfg. Plant	Shipping Weight
Extended Warranties – (See Extended Warranty Section)				
BAYSPEK140B	Single Power Entry Kit	BAYHTR1415BRKB, BAYHTR1419BRKB	VI	5
TAYPLNM100①	Pedestal Plenum Upflow	4TEC3F18-60B1000A	VI	10
TAYBASE101	Downflow Subbase	4TEC3F18-36B1000A	VI	12
TAYBASE100	Downflow Subbase	4TEC3F42-60B1000A	VI	16
BAY99X123	Knockout Cover Plate	4TEC3F18-60B1000A	TR	*

① For TEC018,024,030, center on plenum for 2" difference in width.

* Minimum Order 1 unit (1 unit = 50 pcs.)

Heaters:

Model Number	Power Supply				Mfg. Plant	Shipping Weight
	208/1/60		240/1/60			
	KW	BTUH	KW	BTUH		
BAYHTR1405000	3.60	12,300	4.80	16,400	VI	7
BAYHTR1405BRK	3.60	12,300	4.80	16,400	VI	9
BAYHTR1405PDC	3.60	12,300	4.80	16,400	VI	9
BAYHTR1408000	5.76	19,700	7.68	26,200	VI	8
BAYHTR1408BRK	5.76	19,700	7.68	26,200	VI	9
BAYHTR1408PDC	5.76	19,700	7.68	26,200	VI	9
BAYHTR1410000	7.20	24,600	9.60	32,800	VI	8
BAYHTR1410BRK	7.20	24,600	9.60	32,800	VI	9
BAYHTR1410PDC	7.20	24,600	9.60	32,800	VI	9
BAYHTR1415BRK	11.53	39,300	15.36	52,400	VI	11
BAYHTR1419BRK	14.42	49,200	19.20	65,500	VI	18
BAYHTR1425BRK	18.73	63,900	24.96	85,200	VI	18
	208/3/60		240/3/60			
BAYHTR3410000	7.20	24,600	9.60	32,800	VI	8
BAYHTR3415000	11.53	39,300	15.36	52,400	VI	10

000 = Pigtailed only, BRK = Contains Circuit Breakers, PDC = Pull Disconnect

Features:

- 13.0 SEER
- Ships in a vertical position - convertible for left hand horizontal applications.
- Six- way convertibility-horizontal (left & right); front & rear access; upflow, downflow
- Compact 21" depth for easy installation
- Corrosion resistant galvanized metal with attractive finish
- Easy **Air-Tite™** access to filter
- Superior condensate performance
- Enhanced internally finned coil tubes
- Five ton model with direct drive ECM motor
- Versatile duct flange - allows flush fit 3/4", 1", or 1.5" duct insulation
- Filter panel stamped with word "filter"
- 200/230 volt primary & 24 volt secondary transformer
- Low voltage wire nut connections
- Insulated cabinet
- External access to heater circuit breakers
- Polarized plugs for making electrical connections from air handler control box to heaters
- Factory installed non-bleed TXV with mechanical fitting
- Approved for modular or manufactured homes
- Meets or exceeds Florida's 2% leakage criteria
- **5-year limited parts warranty**
- **Optional extended warranties**