



## OVERVIEW

Sure-Grip 404 is a fiber-free, solvent based, synthetic rubber duct sealant that has passed CDPH in accordance to LEED v4 standards. Its exceptional strength, fast drying time and unmatched flexibility make it ideal for those applications requiring a solvent-based sealant. Sure-Grip's low-viscosity, no-drip, no-string formulation allows fast application for labor savings and extended coverage for lower installed cost.

## PART NUMBERS

302014	1 Case w/ (25) 11-oz. Cartridges
302009	1 Case w/ (4) 1-Gallon Pails
302020	(1) 5-Gallon Pail

## SPECIFICATION/STANDARDS COMPLIANCE

Property	Method	Results
VOC Limitation	ASTM D-2202 11-oz. Cartridges: LEED Compliant	Pass
LEED v4	CDPH Standard Method v1.2 for VOC Emissions	Pass Classroom & Office

## TYPICAL PROPERTIES AND CHARACTERISTICS

Color	Gray
Consistency	Heavy Brush On
Base	Synthetic Rubber Resin
Solvent	Toluene and Heptane
Weight per Gallon	8.8 lbs.
Solids Content	65%
Viscosity	150K - 200K cps
Coverage (per gal.)	Up to 320 lin. ft. at 3" width, 20-mil thickness
Shore A Hardness	> 60
Flexibility	Excellent
Time to Test	24 hours
Service Temperature	-20°F to 200°F
Water Resistance	Excellent
Mildew Resistance	Mold & mildew resistant
VOC	395 g/l
Pressure Class	Up to 20" W.C.
Seal Class	Meets Seal Class A
Freeze/Thaw Stability	Passed 5 Cycles



**APPLICATION**

Temperature	25°F to 100°F (-3.8°C to 38°C) Keep material at room temp prior to use
Method	Brush, putty knife, caulk gun and trowel
Preparation	Surface must be dry and free of dirt, oil and grease.
Rate	Apply at joints and fasteners 20-mil-thick wet film
Clean Up	UN-TACK™ or Solvent (Use safe handling practices.)
Painting	Allow 72 hours, Use only latex or epoxy paints





**PRECAUTIONS**

FLAMMABLE liquid and vapor. Keep away from open flame. May cause flash fire. Contains heptane and toluene solvents. Harmful if swallowed or inhaled. May cause eye irritation. Do not apply this product in areas where intense overexposure is anticipated, or where temperatures will exceed 200°F. Keep out of the reach of children. Review Material Safety Data Sheet for complete safety information prior to use. DO NOT use where acidic or alkaline chemicals are present (ie., lab fume hood, vents, etc.).

**For Industrial Professional Use Only.**

**STORAGE**

Temperature	Below 90°F (32°C)
Shelf Life	One year (unopened)
Flammability	Flammable. Store according to local code.

	<p><b>ADHESIVE</b> Surface Burning Characteristics <b>294U</b> <small>*Applied to inorganic reinforced cement board</small></p>
	<p><b>FLAME SPREAD .....10</b> <b>SMOKE DEVELOPED .....5</b></p> <p><small>*Tested as applied in two 3/8 inch wide strips 8 inches on center at a coverage of 80 sq. ft. per gallon. Flash point of finished adhesive, closed cup: less than minus 14°C.</small></p>
	<p><b>17NF</b> <b>UL 181B-M</b> Mastic closure systems for use with exible duct systems or connectors.</p>

