Eaton FRS-R-25

Catalog Number: FRS-R-25

Eaton Bussmann series FRS-R fuse, 25 A, Dual, Class RK5, Non-indicating, Ferrule end x ferrule end, 10 sec at 500%, 20 kAIC at 300 Vdc, 200 kAIC at 600 V, Standard, 600 V, 300 Vdc

General specifications

Product Name

Eaton Bussmann series FRS-R fuse

UPC

051712508339

Product Height

0.81 in

Product Weight

0.165 lb

Compliances
CE Marked

Catalog Number

FRS-R-25

Product Length/Depth

5 in

Product Width

0.81 in

Warranty

Not Applicable



Powering Business Worldwide

Electrical rating

Amperage Rating

25 A

Interrupt rating

20 kAIC at 300 Vdc 200 kAIC at 600 Vac

Response time

10 sec at 500%

Voltage rating

600 Vac, 300 Vdc

Physical details

Number of elements

Dual

Packaging type

Standard

General information

Class

Class RK5

Connection

Ferrule end x ferrule end

Fuse indicator

Non-indicating

Resources

Catalogs

Bussmann Full Line Catalog

Low Voltage Branch Circuit Fuse Chapter

Compliance information

RoHS Search Tool

Multimedia

Bussmann series Fuseology

Technical service bulletins

Bussmann series FRS-R 600 V Class R up to 60 A fuse data sheet no.

1017



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.

