# **Product Specifications**



# 1/4" Flip Toggle Anchor Kit w/ Pan Head Combo Drive Screws

Part Number FTG14 Category Number 4740 UPC 781002854517

The Flip Toggle Anchor is a single piece, nylon body anchor with a metal tilting head ideal for use in drywall, plaster and hollow wall concrete blocks. It's unique tilting mechanism ensures a trouble-free installation that yields twice the strength of a regular toggle bolt of the same bolt diameter.



# **Physical Characteristics**

Bit	IB2PC
Anchor Type	Flip Toggle
Drive Type	Phillips/Slotted
Head Type	Pan
Screw Size	1/4"-20 x 2-1/2"
Anchor Diameter	1/4"
Thread Per Inch	20
Thread Pitch\Thread Per Inch	1/4"-20
Number of Pieces	10

#### **Packaging Details**

Kit Contains	(10) Flip Toggle Anchors, (10) 1/4"-20 x 2-1/2" Pan Phillips/Slotted Machine Screw	
Standard Qty	1	
Sleeve Qty	0	
Master Qty	10	
Price Per	1	
Package Length	9.60	
Package Width	3.50	
Package Height	1.50	
Net Weight	0.68	
Package Weight	.68	

# **Performance Data**

Tension Strength	1/2" Drywall: 148lbs, 5/8" Drywall: 240lbs, Hollow Concrete Block: 1070lbs	
Safe Tension Load	1/2" Drywall: 74lbs, 5/8" Drywall: 120lbs, Hollow Concrete Block: 535lb	
Shear Strength	1/2" Drywall: 274lbs, 5/8" Drywall: 418lbs, Hollow Concrete Block: 870lbs	
Safe Shear Load	1/2" Drywall: 137lbs, 5/8" Drywall: 209lbs, Hollow Concrete Block: 600lb	
Grip Range	1/2" to 2-1/8"	
Hole Diameter	1/2"	
Applications	Drywall, Hollow Block, Walls, and Ceilings	
Special Features	Twice as Strong as Toggle Bolt, Fast and Easy Installation, Suitable for Overhead Applications, One Strap Design, Only Requires 1/2" Hole, Used with Any Bolt Length up to 3-3/4"	

# Certifications

RoHS Compliant	Yes