MR-LINE

WITH PLASTIC CARRYING CASE

VIDEO BORESCOPE



FEATURES:

- Water resistant IP67 camera head: outer diameter 3.93", with two dimmable LEDS
- Lens: F# 2.8 viewable of angle: 54°, Focal distance: 1-1/4" - 2-1/4"
- 2.4" TFT LCD: 320 x 234 resolution
- 3 buttons operation
- On/Off
- LED light
- Up/Down
- Press Up & Down keys at the same time for turning the picture 180°
- Powered by 4 1.5V AA batteries

SPECIFICATIONS:

Range	Resolution		
Color Mosaic	RGB Bayer Pattern		
Video Format	NTSC Composite Video		
Camera Illumination	2 LEDS, White		
Handler End AVI Port	NTSC Signal Out		
TV Cable Length	Approx. 60"		
Total Length of Device	45" 3/4"		
Metal Tube Length	35" 3/4"		
Diameter of Camera Head	3.93"		

Part [

Description

MA-VID-1 Video Borescope with Case

MA-VID-2 Video Borescope with 10' Extension and Case

Y-VALVE FOR 30# & 50# RECOVERY TANK





REFRIGERANT CYLINDER BAND HEATER

120V, heater draws 200 watts and has 135° preset thermostat
Fits 30 lb., 50 lb., and 125 lb. cylinders

Easy to install and use Safe, built-in thermostat

Part 3054 Description

Refrigerant cylinder Band Heater

2 SPEED-HEAT SHRINK-HEAT GUN

MA02525-3 MA02525-EUKIT

Kit includes:

Heat gun, scraper,

3 different scraper styles and

4 different blower nozzles.



MA02525-2

Lightweight, versatile, flameless heat. On-off switch, 2-speed, 1500 watts. High speed 1100 ° F. Low speed 600° F.

Part Description

MA02525-2 115V, 60 HZ Heat Gun only, North American plug,

UL Listed, CSA and R0HS Compliant

MA02525-3 115V, 60 HZ Heat Gun Kit, North American plug,

UL Listed, CSA and R0HS Compliant

MA02525-EUKIT 230V, 50 HZ Heat Gun Kit, w ith European

Continental Plug, CE Approved and R0HS Compliant




CRANKCASE HEATERS



Girth Dimensions

Part	Description	Min.	Max.	Shape
MA-CH100	240V, 50 Watt	30-3/16	37	Oval
MA-CH101	240V, 54 Watt	27-1/16	34-1/4	Oval
MA-CH101-1	208V, 54 Watt	27-7/16	34-1/4	Oval
MA-CH101-2	120V, 54 Watt	27-1/16	34-1/4	Oval
MA-CH101-3	480V, 54 Watt	27-7/16	34-1/4	Oval
MA-CH102	240V, 60 Watt	25-3/4	32-9/16	Oval
MA-CH102-1	208V, 60 Watt	25-3/4	32-9/16	Oval
MA-CH102-2	120V, 60 Watt	25-3/4	32-9/16	Oval
MA-CH103	240V, 45 Watt	24-3/4	31-9/16	Oval
MA-CH103-2	120V, 45 Watt	24-3/4	31-9/16	Oval
MA-CH135	240V, 45 Watt	28-3/16	35-5/8	Oval

LIQUID LEVEL SWITCHES FOR 30# AND 50# RECOVERY CYLINDERS



These new liquid level switches from the MA-Line have the 80% shut-off feature and are designed to fit the most popular 30# and 50# cylinders available in the market today. Both items have 3-pin Brad Harrison fittings.

Part MA-128500

MA-152540

Description

For 30# or 50# Cylinder, 3-pin Brad Harrison Receptacle. Switch Designed for Worthington and Manchester Cylinders Only Refer to OEM list at right For 26# and 48# Cylinder, 3-pin Brad Harrison Receptacle. Switch Designed for Amtrol Cylinders Only

OEM LIST:
Nat'l Refrigeration
Products (NRP)
Promax n Robinair
Thermal Engineering
Watsco n Penguin
Ridgid (Ridge Tool)
Jameskamm
(Katy Instruments)

Phone: 1-800-956-8220 37 Fax: 1-800-336-8291