

Mueller Streamline Co. Headquarters

150 Schilling Blvd Suite 201 Collierville, Tennessee 38017

Comervine, Tennessee 38017

United States

Phone: 901 753 3200

Mueller Streamline Co. International

525 Okeechobee Blvd Suite 860 West Palm Beach, FL 33401 United States

Phone: 561 273 8300

ITEM # RP01049, ACR PRESS REDUCER, P X P, 1 1/8" X 7/8" OD

Streamline® is the best known, most trusted name in the industry—with a nearly 100-year history of providing the best-inclass products you need to work more e ciently and productively. The ACR Press System is the latest example of the industry-leading innovation and commitment to customer needs that make Streamline® the standard for excellence.



Details | Specifications | Dimensions | Packaging

Details

Approved for use with Type ACR, L, K hard and soft copper tube.

Industry-leading Two Ring Advanced Press (T.R.A.P.) Technology

DualSeal™ Ring Design provides superior sealing and joint strength with 200% more surface contact.

TrapZone™ Leak Barrier innovative vacuum-zone further ensures leak protection.

Force360™ Press Contour provides more uniform joint compression and sealing performance.

Tri-Lock™ Press Profile creates superior joint strength and pressure handling capabilities.

Compatible with R410A and other commonly used refrigerant gases and oils.

Propietary Streamline® ACR Press Jaws available from Milwaukee® Tool.

Compatible with leading full-size press tools on the market.

Includes a 10-year limited warranty against defects in material and workmanship.

Specifications -					
	Weight	0.25 lb			
	Material	COPPER			
	Operating Temperature [Min]	-40 °F			
	Operating Temperature [Max]	250 °F			
	Operating Pressure [Max]	700 psi			
	End Type	ACR Press			
	End Size	1 1/8 in			
	Second End Type	ACR Press			
	Second End Size	7/8 in			

Dimensions

Overall Length	3.13 in
Overall Height	1.50 in
Overall Width	1.50 in
Dimension X	0.31 in

Packaging		-
Qty Pcs / Bag	1	
Master Qty Pcs / Box	60	
UPC Code	685768449003	
Bag GTIN	30685768449004	