

Mueller Streamline Co. Headquarters

150 Schilling Blvd Suite 201 Collierville, Tennessee 38017 United States Phone: 901 753 3200

Mueller Streamline Co. International

525 Okeechobee Blvd Suite 860 West Palm Beach, FL 33401 United States Phone: 561 273 8300

ITEM # RP15726, ACR PRESS SAE ADAPTER, FLARE X P, 3/8" OD

Streamline® is the best known, most trusted name in the industry—with a nearly 100-year history of providing the best-inclass products you need to work more e ciently and productively. The ACR Press System is the latest example of the industry-leading innovation and commitment to customer needs that make Streamline® the standard for excellence.



Details | Specifications | Dimensions | Packaging

Details

Approved for use with Type ACR, L, K hard and soft copper tube.

Industry-leading Two Ring Advanced Press (T.R.A.P.) Technology

DualSeal™ Ring Design provides superior sealing and joint strength with 200% more surface contact.

TrapZone[™] Leak Barrier innovative vacuum-zone further ensures leak protection.

Force360[™] Press Contour provides more uniform joint compression and sealing performance.

Tri-Lock[™] Press Profile creates superior joint strength and pressure handling capabilities.

Compatible with R410A and other commonly used refrigerant gases and oils.

Propietary Streamline® ACR Press Jaws available from Milwaukee® Tool.

Compatible with leading full-size press tools on the market.

Includes a 10-year limited warranty against defects in material and workmanship.

Specifications

Weight	0.13 lb
Material	COPPER
Operating Temperature [Min]	-40 °F
Operating Temperature [Max]	250 °F
Operating Pressure [Max]	700 psi
End Type	ACR Press
End Size	3/8 in
Second End Type	Flare
Second End Size	5/8-18 in

9/10/2024	Page 3 of 3	3
-----------	-------------	---

Overall Length	3.05 in
Overall Height	0.93 in
Overall Width	0.81 in
Dimension X	1.50 in

Packaging

Qty Pcs / Bag	5
Master Qty Pcs / Box	300
UPC Code	685768449157
Bag GTIN	30685768449158