



A CSW Industrials Company

PRODUCT DATA SHEET

SOOTSPRAY™ Aerosol Soot Remover

Description

Sootspray is the original soot remover aerosol. Sootspray clears soot from oil, gas, coal or wood-burning heating units. It reaches where vacuums cannot and causes catalytic burning of soot by reducing ignition point to normal equipment temperatures.

Applications

Sootspray is used to remove soot from oil and gas fired burners. In mobile home units, space heaters, and in all furnaces and boiler systems smaller than apartment house size. Sootspray is carried by the system's natural draft everywhere soot is deposited and helps avoid dismantling hard to reach equipment for soot removal.



DIRECTIONS FOR USE:

READ ALL DIRECTIONS, SDS AND LABEL BEFORE USING

Oil, Gas, Coal and Wood Burners

1. Shut burner off
2. Spray lightly on warm surface. (EXCESS SPRAYING WILL WET THE SOOT AND DELAY THE BURNING PROCESS)
3. Restart burner to ignite and burn off soot. If there is insufficient build-up to ignite the soot, Sootspray's residual action will work when there is slight soot build-up. Some fuels leave a thin, black protective film that has no insulating value.

Note: Contains no petroleum distillates - safe for systems.

For additional technical information, call Toll Free 1-800-231-3345

Characteristics | Features

- Prevents insulating soot from forming
- Improves burner efficiency
- Environmentally friendly

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Feet per Case
68342	14 oz Aerosol (.39 kg)	12	14	0.447

Specifications

Wt/Gal @ 77°F	9.34 lbs/gal
Flash Point SETA CC	Negative Flame Extension, (NFPA) Level 1 Aerosol
Color	Clear
Shelf Life	2 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

Precautionary Statements

Refer to Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300

For additional Technical Information Call Toll Free 1-800-231-3345

Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RectorSeal, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

PO Box 5092 • Hoppers Crossing, VIC 3029, Australia • 07-3267-7277 • rectorseal.com.au

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2021 RectorSeal. All rights reserved. R50490-0421