





Motor Rain Shields

Stock No.	1330A Plastic 1/2" bore	6 ¾" dia	48 FRM
Stock No.	1383A Plastic 5/8" bore	6 ¾" dia	48 FRM
Stock No.	1411A Dished Plastic 1/2" bore	7" dia	48 FRM
Stock No.	1412A Dished Plastic 5/8" bore	7" dia	48 FRM
Stock No.	2097A Plastic 1/2" hore	6" dia	42 FRM

Provides rain protection for vertically mounted motors

Joggle Bolt Mounting Kit

Stock No. 1414A

Provides adjustable casebolt mounting patterns to fit RMR-Fedders (5 %" diameter motors only) and others.





8-32 and 10-32 Case Stud Kit -7" Length

Stock No. 1639A	8-32	
Stock No. 1640A	10-32	

Nuts & Washers —16/Set

Stock No. 1618A	8-32	
Stock No. 1619A	10-32	

Rheem Butt Plate Kit

Stock No. 2098A



Used in place of mounting cables in RHEEM condensers Kit includes mounting hardware and assembly instructions.



Mounting Studs

Stock No.		Ext.	
2064A	8-32	3/4"	Collar Studs for 3 3/8" Dia. Motors
2087A	10-32	1"	Collar Studs for 5" Dia. Motors

Caution:

Threading longest end into motor can create electrical shock or fire hazards, and shorten motor life.



Rubber Vibration Insulating Mount

Type used on Coleman furnaces. See Stock No. 98 & 346

Stock No.	Size	Thread Length
1236A	5⁄8" Dia., 1⁄2" Long	8-32 x ½"

6 Per Pack

