



LOW TEMP BUBBLES

LEAK DETECTOR

DESCRIPTION

LOW TEMP BUBBLES is a leak detector formulated to be used above or below 32° F. Will not harm metals, plastics, rubber or other materials. Suitable for most refrigerants and other natural gas systems. Fluorescent dye in the solution increases visibility of bubbles.

FEATURES AND BENEFITS

- Bubble Action Detects Large or Small Leaks
- Located Pressure Leaks
- Works Above or Below Freezing Temperatures
- Suitable for Most Refrigerants and Natural Gas Systems

SPECIFICATIONS

Form: Green Turbid Liquid | **Odor:** Bland odor | **Boiling Point:** > 212°F (100°C) | **Flammability:** Not considered a flammable liquid by OSHA | **Vapor Pressure (mm Hg):** 20 | **Vapor Density (AIR=1):** > 2 | **Evaporation Rate:** < 1 | **Specific Gravity (H2O=1):** 1.01 | **pH:** 9 | **Solubility in Water:** 100% | **Volatility Including Water (%):** 99% | **Volatility Organic Compounds (VOC):** 0% | **Viscosity:** 135cps

LABEL INFORMATION

LOW TEMP BUBBLES is the ideal solution for detecting large and small leaks. It is specially formulated for above or below freezing temperatures. Suitable for most refrigerants and natural gas systems.

Directions for use : Refer to Material Safety Data Sheet before using. Daub or spray Low Temp Bubbles liberally around suspected leak locations. If leak exists, bubbles will quickly form.

Note: Wipe the surface to be tested before daubing to avoid contaminating liquid when putting the dauber back into the bottle.

Dangers: Read and understand the product's label and Safety Data Sheet. Do not take internally. Avoid contact with eyes. Causes eye irritation. May cause skin irritation in rare cases. May cause gastrointestinal irritation.

DO NOT use in any manner for which it was not designed. Always wear safety glasses when when applying product.

PLEASE REFER TO SDS TO VIEW SPECIFIC INFORMATION REGARDING WARNING SYMBOLS AND HMIS/NFPA CODES.

CONTAINS

LOW TEMP BUBBLES CONTAINS (CAS#) : Water (7732-18-5), Surfactant (67785-13-1), Ethylene Glycol (107-21-1)

VAPCO PART NO.

Part Number	Size
LDL-1	1 gallon 4/cs
LDL-1/2P	8 oz 12/cs
LDL-1Q	32 oz 12/cs

First Aid Measures

Inhalation: Move to fresh air.

Skin contact: Immediately wash with soap and water for 15 minutes.

Eye Contact: Remove contact lenses if present. Flush with water for at least 15 minutes. **See Physician if irritation persists.**

Ingestion: Rinse mouth with water. Do NOT induce vomiting unless directed by medical authority. **See Physician if irritation persists.**

Precautions

Do NOT handle or use this product until all safety precautions have been read and understood. Do not take internally. Avoid contact with eyes. Wash hands and arms thoroughly after handling. Wear protective eye wear such as safety glasses when applying.

Storage

Keep out of reach of children. Minimize temperature extremes. Keep containers closed when not in use. Do not transfer to unmarked containers. Loosen closure carefully. Keep from freezing.

In Case of Fire

Non-combustible. Will not burn or support combustion. Use water or appropriate media for surrounding fire.

Disposal

Dispose of contents in accordance with local/regional/national regulations. Non-hazardous.