

## 8-WAY™ Boiler Water Conditioner

### Description

8-WAY is a complete boiler water treatment for steam and hot water systems. Removes sludge and rust scale, inhibits boiler corrosion, steam line corrosion and lime scale. Prevents oxygen pitting, surging and foaming. Controls pH with color indicator.

### Applications

8-Way is a protective maintenance for steam and hot water heating systems. Recommended for cleaning very dirty steam boilers, boilers with excessive scale, rust and must. 8-Way can be used to maintain clean, rust free water on new or existing systems.

### Instructions for Use

#### READ ALL DIRECTIONS, SDS AND LABEL BEFORE USING

**Steam Boiler** (1) Pour or pump 8-Way into boiler until water turns violet in color. One quart typically treats up to 30 gallons water content - approximately 600 sq. ft. of radiation, or 5.5B.H.P. (2) Allow to steam for 1/2 to 3 hours, then drain and flush. (3) Refill boiler water and add 1 qt. of 8-way for each qt. originally used. 8-Way remains in the system to inhibit surging and corrosion. **New Steam Boiler** installation, add 8-way until water turns blue or violet. Leave in system to condition water for one full season. **Hot Water Boiler** use 1 qt 8-way for each 25 gallons of circulating water. **Sure-cure color indicator** - Light blue green (insufficient dosage) Violet (cleaning dosage) Blue or Violet (scale prevention dosage).

For additional technical information, call Toll Free 1-800-231-3345

**WARNING:** Not compatible with aluminum.



### Characteristics | Features

- Builds alkalinity
- Controls pH
- Inhibits corrosion
- Sure-cure color indicator

### Packaging

| Code  | Size                 | Qty. per Case | Lbs. per Case | Cubic Ft per Case |
|-------|----------------------|---------------|---------------|-------------------|
| 68712 | Quart (.946 l)       | 12            | 31            | 0.71              |
| 68714 | Gallon (3.79 l)      | 4             | 42            | 1.27              |
| 68716 | 30 Gallons (113.5 l) | 1             | 296           | NA                |

**Specifications**

|                     |                            |
|---------------------|----------------------------|
| Wt/Gal @ 77°F       | 9.2 lbs/gal                |
| Flash Point SETA CC | None                       |
| Color               | Dark blue or purple liquid |
| Shelf Life          | 3 years                    |

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances



**DANGER!**

Causes severe skin burns and serious eye damage.  
May be harmful if swallowed.  
May be corrosive to metals.

**Precautionary Statements**

Refer to Safety Data Sheet (SDS).

**KEEP OUT OF REACH OF CHILDREN.**

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300.**

For additional information Call Toll Free 1-800-231-3345.

**Limited Warranty**



For more information on our product limited warranty, visit [RectorSeal.com](http://RectorSeal.com)

Distributed by

**RectorSeal, LLC**

**2601 Spenwick Drive, Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • [rectorseal.com](http://rectorseal.com)**

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2024 RectorSeal. All rights reserved. R50490-0424